

VALVE SPECIFICATIONS

Year	Engine ID/VIN	Engine Displacement Liters (cc)	Seat Angle (deg.)	Face Angle (deg.)	Spring Test Pressure (lbs. @ in.)	Spring Installed Height (in.)	Stem-to-Guide Clearance (in.)		Stem Diameter (in.)	
							Intake	Exhaust	Intake	Exhaust
							1994	U	3.0 (2971)	45
	Y	3.0 (2980)	45	45.5	121 @ 1.19	1.760 1	0.0010- 0.0023	0.0012- 0.0025	0.2346- 0.2352	0.2344- 0.2350
	P	3.2 (3191)	45	45.5	121 @ 1.19	1.760 1	0.0010- 0.0023	0.0012- 0.0025	0.2346- 0.2352	0.2344- 0.2350
	4	3.8 (3802)	44.5	45.8	220 @ 1.18	1.970	0.0010- 0.0028	0.0015- 0.0033	0.3415- 0.3423	0.3410- 0.3418
1995	U	3.0 (2980)	45	44	180 @ 1.16	1.580	0.0001- 0.0028	0.0015- 0.0033	0.3126- 0.3134	0.3121- 0.3129
	Y	3.0 (2980)	45	45.5	121 @ 1.19	1.760 1	0.0010- 0.0023	0.0012- 0.0025	0.2346- 0.2352	0.2344- 0.2350
	P	3.2 (3191)	45	45.5	121 @ 1.19	1.760 1	0.0010- 0.0023	0.0012- 0.0025	0.2346- 0.2352	0.2344- 0.2350
	4	3.8 (3802)	44.5	45.8	220 @ 1.18	1.970	0.0010- 0.0028	0.0015- 0.0033	0.3415- 0.3423	0.3410- 0.3418

1: Approximate Free Length