

# TORQUE SPECIFICATIONS

Component	US	Metric
Flexible Fuel (FF) Sensor		
3.0L Flexible Fuel (FF) Engines only	27-34 inch lbs.	3-4 Nm
Fuel Injection Supply Manifold		
SFI		
3.0L (except SHO)	6-9 ft. lbs.	8-12 Nm
3.0L/3.2L SHO	11-17 ft. lbs.	15-23 Nm
3.8L	6-8 ft. lbs.	8-11 Nm
Fuel Pressure Regulator		
CFI	27-35 inch lbs.	3.1-3.9 Nm
EFI	34 inch lbs.	3.8 Nm
SFI		
3.0L (except SHO) and 3.8L	34 inch lbs.	3.8 Nm
3.0L/3.2L SHO	18-25 ft. lbs.	25-34 Nm
Fuel Pressure Relief Valve		
CFI	4-6 inch lbs.	0.5-0.7 Nm
EFI		
Valve	66 inch lbs.	7.4 Nm
Cap	5.5 inch lbs.	0.6 Nm
SFI		
Valve	69 inch lbs.	7.75 Nm
Cap	5.5 inch lbs.	0.6 Nm
Fuel Rail Assembly		
EFI		
2.5L	15-22 ft. lbs.	20-30 Nm
3.0L (except SHO) and 3.8L	7 ft. lbs.	10 Nm
Fuel Tank		
Strap Retaining Bolts	22-30 ft. lbs.	29-41 Nm
Hose Pipe Clamps	24-32 inch lbs.	2.7-3.7 Nm
Idle Air Bypass Valve	84 inch lbs.	9.5 Nm
Idle Air Control Valve		
3.0L (except SHO) and 3.8L	84 inch lbs.	9.5 Nm
3.0L/3.2L SHO	63-97 inch lbs.	7-11 Nm
Injector		
CFI	18-22 inch lbs.	2.0-2.5 Nm
Throttle Body		
CFI		
2.5L	15-25 ft. lbs.	20-34 Nm
EFI		
2.5L	12-15 ft. lbs.	16-20 Nm
3.0L (except SHO)	15-22 ft. lbs.	20-30 Nm