

WHEEL ALIGNMENT

Year	Model		Caster		Camber		Toe-in (in.)	Steering Axis Inclination (deg.)
			Range (deg.)	Preferred Setting (deg.)	Range (deg.)	Preferred Setting (deg.)		
1992 (cont.)	Sable	F 2	2 11/16P-4 11/16P	3 11/16P	1N-1/4P	3/8N	3/32N	15 1/2
		R 2	-	-	1 5/8N-7/32N	15/16N	1/16P	-
1993	Taurus	F 1	2 13/16P-5 13/16P	2 13/16P	1 1/8N-1/8P	1/2N	3/32N	15 1/2
		F 2	2 11/16P-4 11/16P	3 11/16P	1N-1/4P	3/8N	3/32N	15 1/2
	Taurus	R	-	-	1 5/8N-7/32N	15/16N	1/16P	-
	Sable	F 1	2 13/16P-5 13/16P	2 13/16P	1 1/8N-1/8P	1/2N	3/32N	15 1/2
		R 1	-	-	1 5/8-7/32N	15/16N	1/16P	-
Sable	F 2	2 11/16P-4 11/16P	3 11/16P	1N-1/4P	3/8N	3/32N	15 1/2	
	R 2	-	-	1 5/8N-7/32N	15/16N	1/16P	-	
1994	Taurus	F 1	2.81P-4.81P	3.81P	1.13N-0.13P	0.50N	0.09N	15.50
		R 2	-	-	1.60N-0.20N	0.90N	0.06P	-
	Taurus	F 1	2.70P-4.70P	3.70P	1.00N-0.20N	0.40N	0.20N	15.50
		R 2	-	-	1.90N-0.10P	0.90N	0.06P	-
Sable	F 1	2.80P-4.80P	3.80P	1.10N-0.010P	0.50N	0.20N	15.50	
	R 1	-	-	1.60N-0.20N	0.90N	0.06P	-	
1995	Taurus	F 1	2.80P-4.80P	3.80P	1.10N-0.10P	0.50N	0.20N	15.50
		R	-	-	1.60N-0.20N	0.90N	0.06P	-
	Taurus	F 2	2.70P-4.70P	3.70P	1.00N-0.20N	0.40N	0.20N	15.50
		R	-	-	1.90N-0.10P	0.90N	0.06P	-
Sable	F 1	2.80P-4.80P	3.80P	1.10N-0.10P	0.50N	0.20N	15.50	
	R	-	-	1.60N-0.20N	0.90N	0.06P	-	
Sable	F 2	2.70P-4.70P	3.70P	1.00N-0.20N	0.40N	0.20N	15.50	
	R	-	-	1.90N-0.10P	0.90N	0.06P	-	

P - Positive
 N - Negative
 F - Front
 R - Rear

1 Sedan
 2 Wagon