

# BRAKE SPECIFICATIONS

All measurements in inches unless noted

Year	Model		Master Cylinder Bore	Brake Disc			Brake Drum Diameter			Minimum Lining Thickness	
				Original Thickness	Minimum Thickness	Maximum Runout	Original Inside Diameter	Max. Wear Limit	Maximum Machine Diameter	Front	Rear
1986	Taurus	1	0.875	NA	0.896	0.002	8.86	8.93	8.92	0.125	0.030
	Taurus	2	0.875	NA	0.896	0.002	9.84	9.99	9.90	0.125	0.030
	Sable	1	0.875	NA	0.896	0.002	8.86	8.93	8.92	0.125	0.030
	Sable	2	0.875	NA	0.896	0.002	9.84	9.99	9.90	0.125	0.030
1987	Taurus	1	0.875	NA	0.896	0.002	8.86	8.93	8.92	0.125	0.030
	Taurus	2	0.875	NA	0.896	0.002	9.84	9.89	9.90	0.125	0.030
	Sable	1	0.875	NA	0.896	0.002	8.86	8.93	8.92	0.125	0.030
	Sable	2	0.875	NA	0.896	0.002	9.84	9.89	9.90	0.125	0.030
1988	Taurus	1	0.875	NA	0.896	0.002	8.86	8.93	8.92	0.125	0.030
	Taurus	2	0.875	NA	0.896	0.002	9.84	9.89	9.90	0.125	0.030
	Sable	1	0.875	NA	0.896	0.003	8.86	8.93	8.92	0.125	0.030
	Sable	2	0.875	NA	0.896	0.002	9.84	9.89	9.90	0.125	0.030
1989	Taurus	1	0.875	NA	0.896	0.002	8.86	8.93	8.92	0.125	0.030
	Taurus	2	0.875	NA	0.896	0.002	9.84	9.89	9.90	0.125	0.030
	Taurus SHO	F	0.875	NA	0.972	0.002	-	-	-	0.125	0.030
	Taurus SHO	R	-	-	0.900	0.002	-	-	-	-	0.123
	Sable	1	0.875	NA	0.896	0.002	8.86	8.93	8.92	0.125	0.030
	Sable	2	0.875	NA	0.896	0.002	9.84	9.89	9.90	0.125	0.030
1990	Taurus	1	0.875	NA	0.972	0.002	8.86	8.93	8.92	0.125	0.030
	Taurus	2	0.875	NA	0.972	0.002	9.84	9.89	9.90	0.125	0.030
	Taurus SHO	F	0.875	NA	0.972	0.002	-	-	-	0.125	0.030
	Taurus SHO	R	-	-	0.900	0.002	-	-	-	-	0.123
	Sable	F	1.000	1.024	0.997	0.003	<sup>8</sup>	NA	<sup>9</sup>	0.125	0.030
	Sable	R	-	0.940	0.900	0.002	-	-	-	-	0.123
1991	Taurus	1	F 0.875	NA	0.972	0.002	8.86	8.93	8.92	0.125	0.030
	Taurus	2	F 0.875	NA	0.972	0.002	9.84	9.89	9.90	0.125	0.030
	Taurus SHO	F	0.875	NA	0.972	0.002	-	-	-	0.125	-
	Taurus SHO	R	-	-	0.900	0.002	-	-	-	-	0.123
	Sable	F	1.000	1.024	0.974	0.003	<sup>8</sup>	NA	<sup>9</sup>	0.125	0.030
	Sable	R	-	0.940	0.900	0.002	-	-	-	-	0.123
1992	Taurus	1	0.875	NA	0.972	0.002	8.86	8.93	8.92	0.125	0.030
	Taurus	2	0.875	NA	0.972	0.002	9.84	9.89	9.90	0.125	0.030
	Taurus SHO	<sup>3</sup>	0.875	NA	0.972	0.002	-	-	-	0.125	-
	Taurus SHO	<sup>4</sup>	-	-	0.900	0.002	-	-	-	-	0.123
	Sable	F	1.000	1.024	0.974	0.003	<sup>8</sup>	NA	<sup>9</sup>	0.125	0.030
	Sable	R	-	0.940	0.900	0.002	-	-	-	-	0.123
1993	Taurus	1	0.875	NA	0.972	0.002	8.86	8.93	8.92	0.125	0.030
	Taurus	2	0.875	NA	0.972	0.002	9.84	9.89	9.90	0.125	0.030
	Taurus SHO	F	0.875	NA	0.972	0.002	-	-	-	0.125	-
	Taurus SHO	R	-	-	0.900	0.002	-	-	-	-	0.123
	Sable	F	1.000	1.024	0.974	0.003	<sup>8</sup>	NA	<sup>9</sup>	0.125	0.030
	Sable	R	-	0.940	0.900	0.002	-	-	-	-	0.123
1994	Taurus		1.000	<sup>5</sup>	<sup>6</sup>	<sup>7</sup>	<sup>8</sup>	NA	<sup>9</sup>	0.040	<sup>10</sup>
	Taurus SHO		1.000	<sup>5</sup>	<sup>6</sup>	<sup>7</sup>	-	-	-	0.040	0.123
	Sable	F	1.000	1.020	0.974	0.003	<sup>8</sup>	NA	<sup>9</sup>	0.125	0.030