

BRAKE SPECIFICATIONS

All measurements in inches unless noted

Year	Model		Master Cylinder Bore	Brake Disc			Brake Drum Diameter			Minimum Lining Thickness	
				Original Thickness	Minimum Thickness	Maximum Runout	Original Inside Diameter	Max. Wear Limit	Maximum Machine Diameter	Front	Rear
1994	Sable	R	-	0.940	0.900	0.002	-	-	-	-	0.123
1995	Taurus		1.000	5	6	7	8	NA	9	0.040	10
	Taurus SHO		1.000	5	6	7	-	-	-	0.040	0.123
	Sable	R	-	0.940	0.900	0.002	-	-	-	-	0.123
	Sable	R	-	-	-	-	8	NA	4	-	0.030

NOTE: Follow specifications stamped on rotor or drum if figures differ from those in this chart.

NA - Not Available

F - Front

R - Rear

1 Sedan

2 Wagon

3 Except rear disc

4 With rear disc

5 Front: 1.020

Rear: 0.940

6 Front: 0.974

Rear: 0.500

7 Front: 0.003

Rear: 0.002

8 Sedan: 8.85

Wagon: 9.84

9 Sedan: 8.91

Wagon: 9.90

10 With disc brakes: 0.123

With drum brakes: 0.030