Hood, Trunk Lid, Hatch Lid, Glass and Doors

Possible Cause

Correction

Problem

HOOD/TRUNK/HATCH LID		
Improper closure.	 Striker and latch not properly aligned. 	· Adjust the alignment.
Difficulty locking and unlocking.	 Striker and latch not properly aligned. 	 Adjust the alignment.
Uneven clearance with body panels.	 Incorrectly installed hood or trunk lid. 	 Adjust the alignment.
WINDOW/WINDSHIELD GLASS		
Water leak through windshield	Defective seal.Defective body flange.	Fill sealantCorrect.
Water leak through door window glass.	 Incorrect window glass installation. 	 Adjust position.
	 Gap at upper window frame. 	 Adjust position.
Water leak through quarter	• Defective seal.	• Replace seal.
window.	Defective body flange.	· Correct.
Water leak through rear window.	Defective seal.Defective body flange.	Replace seal.Correct.
FRONT/REAR DOORS		
Door window malfunction.	 Incorrect window glass installation. 	 Adjust position.
	 Damaged or faulty regulator. 	 Correct or replace.
Water leak through door edge.	 Cracked or faulty weatherstrip. 	· Replace.
Water leak from door center.	 Drain hole clogged. Inadequate waterproof skeet contact or damage. 	Remove foreign objects.Correct or replace.
Door hard to open.	 Incorrect latch or striker adjustment. 	· Adjust.
Door does not open or close completely.	· Incorrect door installation.	· Adjust position.
	 Defective door check strap. Door check strap and hinge require grease. 	Correct or replace.Apply grease.
Uneven gap between door and body.	· Incorrect door installation.	· Adjust position.
Wind noise around door.	 Improperly installed weatherstrip. 	Repair or replace.
	 Improper clearance between door glass and door weatherstrip. 	• Adjust.
	Deformed door.	Repair or replace.